



Surface-Mount D-Ring · 2-Pack

5,000lb Heavy-Duty Surface-Mount D-Ring 2pk

SAFE WORKING LOAD · BREAK STRENGTH
1,667 lb / 5,000 lb · per D-ring

Model	D3008 (2-pack)
Product Type	Heavy-duty surface-mount D-ring
Rated Capacity	5,000-lb break strength per D-ring
Construction	Zinc-plated steel ring and mounting plate
Mounting	Two-hole surface-mount plate
Brand Marking	5,000 LB stamped on plate; VINLOC retail packaging

Key Features

Heavy-Duty Surface-Mount Point

Heavy-duty D-ring provides a robust attachment point on compatible cargo floors, walls, trailers, and utility surfaces when correctly installed.

Zinc-Plated Steel Construction

Zinc-plated steel components support durability and help resist corrosion in general cargo-control environments.

Unified VINLOC Retail Packaging

Consistent VINLOC branding, coordinated red-and-black graphics, and clear model identification create a cohesive, professional presentation across the product range.

Folding Low-Profile Ring

Hinged ring folds toward the mounting surface when not in use to reduce obstruction and simplify storage.

Two-Hole Mounting Plate

Dual square mounting holes distribute attachment across the steel base for secure installation with application-appropriate fasteners.

2-Pack Value

Two D-rings per retail pack support matched-point installation or convenient replacement across compatible cargo areas.