



Surface-Mount D-Ring · 1-Pack

11,000lb Heavy-Duty Surface-Mount D-Ring 1pk

SAFE WORKING LOAD · BREAK STRENGTH
3,667 lb / 11,000 lb · per D-ring

Model	D3011 (single pack)
Product Type	Heavy-duty surface-mount D-ring
Rated Capacity	11,000-lb minimum break strength per D-ring
Construction	Yellow zinc-plated steel ring and mounting plate
Mounting	Two-hole surface-mount plate
Brand Marking	11,000 LB MBS printed on ring; VINLOC retail packaging

Key Features

High-Capacity Surface-Mount Point

High-capacity D-ring provides a robust attachment point on compatible cargo floors, walls, trailers, and utility surfaces when correctly installed.

Yellow Zinc-Plated Steel

Yellow zinc-plated steel components support durability and help resist corrosion in general cargo-control environments.

Unified VINLOC Retail Packaging

Consistent VINLOC branding, coordinated red-and-black graphics, and clear model identification create a cohesive, professional presentation across the product range.

Folding Low-Profile Ring

Hinged ring folds toward the mounting surface when not in use to reduce obstruction and simplify storage.

Two-Hole Mounting Plate

Dual square mounting holes distribute attachment across the steel base for secure installation with application-appropriate fasteners.

Single-Pack Convenience

One D-ring per retail pack supports focused installation or convenient replacement across compatible cargo areas.